



DISTRIBUIDO POR



+54 11 15 6398 0580 / 15 5315 6982

## FLOODED DEEP CYCLE BATTERY

## 6 CS 17P



Series	5000	Warranty	See Warranty Terms
Volts	6	BCI	SPEC
Cells	3	Plates/Cell	17
Terminal Type	Flag RR		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18 x 1-1/2"		
Cables	19" 4/0 interconnect cables *RE incl.		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25-2.3 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	1393
Marine Crank Amps (MCA) 32°F / 0°C	1742
Reserve Capacity (RC @ 25A)	1310 Minutes
Reserve Capacity (RC @ 75A)	437 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPS
@ 100 Hour Rate	<b>770 AH</b>	<b>7.7 A</b>
@ 75 Hour Rate	<b>566 AH</b>	<b>7.87 A</b>
@ 50 Hour Rate	<b>524 AH</b>	<b>10.48 A</b>
@ 20 Hour Rate	<b>546 AH</b>	<b>27.3 A</b>
@ 15 Hour Rate	<b>508 AH</b>	<b>33.85 A</b>
@ 10 Hour Rate	<b>453 AH</b>	<b>45.32 A</b>
@ 8 Hour Rate	<b>426 AH</b>	<b>53.24 A</b>
@ 5 Hour Rate	<b>366 AH</b>	<b>73.16 A</b>
@ 1 Hour Rate	<b>186 AH</b>	<b>185.64 A</b>

Ampere hour capacity ratings based on specific gravity of 1.280. Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications

Certified System




SAI GLOBAL  
ISO 9001  
Quality

Weight	100 kg	220.5 lbs
Length	55.9 cm	22"
Width	21 cm	8.25"
Height Inc. Term.	46.4 cm	18.25"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene- heatsealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

