



DISTRIBUIDO POR



+54 11 15 6398 0580 / 15 5315 6982

## FLOODED DEEP CYCLE BATTERY

**6 CS 25P**



Series	5000	Warranty	See Warranty Terms
Volts	6	BCI	SPEC
Cells	3	Plates/Cell	25
Terminal Type	Flag RR		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18 x 1-1/2"		
Cables	19" 4/0 interconnect cables *RE incl.		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	2090
Marine Crank Amps (MCA) 32°F / 0°C	2612
Reserve Capacity (RC @ 25A)	1968 Minutes
Reserve Capacity (RC @ 75A)	656 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPS
@ 100 Hour Rate	<b>1156 AH</b>	<b>11.56 A</b>
@ 75 Hour Rate	<b>851 AH</b>	<b>11.81 A</b>
@ 50 Hour Rate	<b>787 AH</b>	<b>15.73 A</b>
@ 20 Hour Rate	<b>820 AH</b>	<b>41 A</b>
@ 15 Hour Rate	<b>763 AH</b>	<b>50.84 A</b>
@ 10 Hour Rate	<b>681 AH</b>	<b>68.06 A</b>
@ 8 Hour Rate	<b>640 AH</b>	<b>79.95 A</b>
@ 5 Hour Rate	<b>549 AH</b>	<b>109.88 A</b>
@ 1 Hour Rate	<b>279 AH</b>	<b>278.8 A</b>

Ampere hour capacity ratings based on specific gravity of 1.280. Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications

Certified System




SAI GLOBAL  
ISO 9001  
Quality

Weight	144 kg	317.5lbs
Length	55.9cm	22"
Width	28.6cm	11.25"
Height Inc. Term.	46.4cm	18.25"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene - heatsealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

