



DISTRIBUIDO POR



+54 11 15 6398 0580 / 15 5315 6982

OPzV GEL DEEP CYCLE BATTERY

S2-1380GEL



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type		F10	
Included Hardware		Threaded Insert & Bolt	
Size & Thread		F10-M10	

Charge

Charge Voltage Range	2.38 V/cell @ 25°C (77°F)
Float Voltage Range	2.28 V/cell @ 25°C (77°F)
Recommended Charge Current Capacity (String)	120 A
Maximum Charge Current (String)	360 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	0.24 mΩ

Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPS
@ 100 Hour Rate	1938 AH	19.38 A
@ 20 Hour Rate	1571 AH	78.55 A
@ 10 Hour Rate	1380 AH	138 A

Specifications




SAI GLOBAL
ISO 9001
Quality

Weight	97kg	214 lbs
Length	27.5 cm	10.83"
Width	21 cm	8.27"
Height Inc. Term.	67.3 cm	26.5"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	None

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature

