

Rolls

DISTRIBUIDO POR

KONNEKTO
ENERGY

+54 11 15 6398 0580 / 15 5315 6982

OPzV GEL DEEP CYCLE BATTERY

S2-567GEL



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type		F10	
Included Hardware		Threaded Insert & Bolt	
Size & Thread		F10-M10	

Charge

Charge Voltage Range	2.38 V/cell @ 25°C (77°F)
Float Voltage Range	2.28 V/cell @ 25°C (77°F)
Recommended Charge Current Capacity (String)	49A
Maximum Charge Current (String)	147 A
Self-Discharge Rate	Less than 2% per month at 20°C (68°F)
Internal Resistance	0.45 mΩ

Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%
Hour Rate	Capacity / AMP Hour	Current / AMPs		
@ 100 Hour Rate	782 AH	7.82 A		
@ 20 Hour Rate	643 AH	32.15 A		
@ 10 Hour Rate	567 AH	56.7 A		

Specifications




SAI GLOBAL
ISO 9001
Quality

Weight	42kg	92.5lbs
Length	16.6cm	6.54"
Width	20.6cm	8.11"
Height Inc. Term.	49.8cm	19.61"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	None

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature

